ULTRASTRONG ESD FLOOR MATTING Mission Critical Static Dissipative Floor Mats



UltraStrong advanced three layer ESD floor mats provide the utmost in antistatic protection. This easy to clean static control matting is highly resistant to abrasion, tears and cracking.

UltraStrong is recommended for use over hard surface floors such as Vinyl, VCT, Concrete etc. (Note: not recommended for use on carpet).

UltraStrong provides years' worth of ESD protection without fading or leaving residue on your existing floor.
UltraStrong handles chair caster traffic and carts without tearing, cracking or delaminating.

UltraStrong's advanced Tri-Layer composition feature a static dissipative top layer bonded to a conductive inner scrim bonded to a static dissipative bottom layer for Ultimate static control protection.

UltraStrong 187-AS is fully warranted to meet the latest ANSI/ESD S20.20 standards having

successfully passed its page 4, Table 2, Product Qualification as tested to ANSI/ESD STM97.1, ANSI//ESD STM97.1 and Table 3 Page 6 ANSI/ESD STM7.1 test methods.

- Resistant to cuts, tears, and impact.
- Resistant to ozone damage, fire, and most chemicals.
- Easy to clean sweep or hose off.
- Weight: 0.8 lbs. per SF Min
- Color: Dark Gray
- Electrical Properties:
- PTP: >1.0E06 <1.0E09
- RTG: >1.0E06 <1.0E09
- Typical: 5x10⁷ @ 38% rH and 72° F.
- RTG inner layer: <1.0E05
- Includes Heavy Duty Floor Mat Ground Cord

PHYSICAL PROPERTIES:

Material Composition: Vinyl with silver coated fiber (internal scrim).

Part Number: 187-AS Thickness: 3/32 of an inch

Colors: Dark Gray

Availability: Widths; 2 foot, 30 inch, 3 and 4 feet. Lengths; Up to 75 feet. Full rolls and custom cut sizes.

DISTRIBUTED BY:

ULTRASTRONG ESD FLOOR MATTING Mission Critical Static Dissipative Floor Mats

Available Color

